



**ENGINEERED TO PERFORM. BUILT TO LAST.**

Reliable lift systems for independent repair shops, car dealerships, bodyshops, home enthusiasts, and heavy-duty truck facilities.

# F10

**LIGHT DUTY TWO POST LIFT**  
10,000 lbs. Capacity

## FEATURES:

Symmetrical column design

Versatile 3-stage front and 2-stage rear arms

- Top mounted Direct-Pull lifting technology
- Cylinder rod concealed inside carriage
- Adjustable width options
- Optional extended height kit adds 2'
- Single point lock release
- Powder coated finish
- Includes adapter storage bracket
- ALI Certified

**INCLUDES LOW-PROFILE DROP-IN ADAPTERS AND (4 each) ADAPTER EXTENSIONS AT 3.5" and 5"**



Forward Lifts meet the highest industry safety and performance standards. Your assurance of certification is the gold ALI/ETL certified label.




FWD F10N400MBL

## T100295 Extended Height Kit

The column extension kit is used to add an additional 2 feet (609.6 mm) to the top of the standard lift. This kit includes an extended length hose, return line, and cables to accommodate the extended height. Existing hardware included with the lift is used to attach the extensions.

This kit can be used on the current 400 series model F10 Forward Two Post Lifts.



996 Industrial Drive  
Madison, IN 47250

Phone: 800.423.1722  
Fax: 812.273.7329



[www.forwardlift.com](http://www.forwardlift.com)



Lit# Forward F10 CUTSHEET.2021.02 ©2021 Vehicle Service Group™ All rights reserved.

Unless otherwise indicated, Forward Lift, Vehicle Service Group™, Dover and all other trademarks are property of Dover Corporation and its affiliates. Printed in the U.S.A.

SPECIFICATIONS	F10N400MBL/RD*
Capacity	10,000 lbs. (4535kg)
Maximum Rise	76 - 1/4" (1937mm) w / 5" extension
Overall Height	143" or optional 167" ** (3632mm/4241mm)
Overall Width	131" or optional 137" (3327mm/3480mm)
Drive through Clearance	99" or optional 105" (2515mm/2667mm)
Overhead Switch Height	137-1/4" (3486mm)
Front Reach (Min/Max)	24-1/2" / 44-3/8" (621mm/1127mm)
Rear Reach (Min/Max)	36" / 58" (914mm/1473mm)
Min/Max Adapter Height	3-3/4" (95mm) w/o adapter extension 8-3/4" (222mm) w / 5" adapter extension
Width Inside Columns	109" or optional 115" (2769mm/2921mm)
Voltage/ Amps	208V/230V, 17 amps
Motor/Phase	1ph/2HP/60Hz
Ceiling Height Required	144" (3658mm)

\*Lifts available in blue and red \*\*With T100295 Extended Height Kit Specifications subject to change without notice or liability.